

Safety Data Sheet

MITAN Mineralöl GmbH

Alpine Brake Fluid DOT 4

Revision date: 17.03.2021

Product code: MIT0044

Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Alpine Brake Fluid DOT 4

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

brake fluids

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Company name:	MITAN Mineralöl GmbH	
Street:	Industriestraße 8	
Place:	D-49577 Ankum	
Telephone:	+49 (0)5462/7470-50	Telefax: +49 (0)5462/7470-33
e-mail:	info@mitan-oil.de	
e-mail (Contact person):	sicherheitsdatenblatt@mitan-oil.de	
Internet:	www.mitan-oil.de	

1.4. Emergency telephone number:

Giftinformationszentrum Nord (Göttingen)
+49 (0)551/19240

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Reproductive toxicity: Repr. 2

Hazard Statements:

Suspected of damaging the unborn child.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate

Signal word: Warning

Pictograms:



Hazard statements

H361d Suspected of damaging the unborn child.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Safety Data Sheet

MITAN Mineralöl GmbH

Alpine Brake Fluid DOT 4

Revision date: 17.03.2021

Product code: MIT0044

Page 2 of 15

P308+P313 IF exposed or concerned: Get medical advice/attention.
P405 Store locked up.
P501 Dispose of contents / container in accordance with official regulations.

Special labelling of certain mixtures

EUH208 Contains Dihydro-3-(tetrapropenyl)furan-2,5-dione. May produce an allergic reaction.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	GHS Classification	
30989-05-0	Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate	< 30 %
	250-418-4	
	01-2119462824-33	
	Repr. 2; H361d	
111-46-6	2,2'-oxybisethanol; diethylene glycol	< 10 %
	203-872-2	
	603-140-00-6	
	01-2119457857-21	
	Acute Tox. 4; H302	
143-22-6	2-[2-(2-butoxyethoxy)ethoxy]ethanol	< 10 %
	205-592-6	
	603-183-00-0	
	01-2119475107-38	
	Eye Dam. 1; H318	
111-77-3	2-(2-methoxyethoxy)ethanol	< 3 %
	203-906-6	
	603-107-00-6	
	01-2119475100-52	
	Repr. 2; H361d	
26544-38-7	Dihydro-3-(tetrapropenyl)furan-2,5-dione	< 0,1 %
	247-781-6	
	01-2119979080-37	
	Eye Irrit. 2, Skin Sens. 1A, Aquatic Chronic 4; H319 H317 H413	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
30989-05-0	250-418-4	Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate	< 30 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2000 mg/kg	
111-46-6	203-872-2	2,2'-oxybisethanol; diethylene glycol	< 10 %
		dermal: LD50 = 11890 mg/kg; oral: LD50 = 16500 mg/kg	
143-22-6	205-592-6	2-[2-(2-butoxyethoxy)ethoxy]ethanol	< 10 %
		dermal: LD50 = 3540 mg/kg Eye Dam. 1; H318: >= 30 - 100 Eye Irrit. 2; H319: >= 20 - < 30	
111-77-3	203-906-6	2-(2-methoxyethoxy)ethanol	< 3 %
		inhalation: LC50 = > 200 mg/l (vapours); dermal: LD50 = 9404 mg/kg; oral: LD50 = 7128 mg/kg	

SECTION 4: First aid measures

Safety Data Sheet**Alpine Brake Fluid DOT 4**

Revision date: 17.03.2021

Product code: MIT0044

Page 3 of 15

4.1. Description of first aid measures**General information**

Personal protection equipment: see section 8
Never give anything by mouth to an unconscious person or a person with cramps.
In all cases of doubt, or when symptoms persist, seek medical advice.

After inhalation

Remove person to fresh air and keep comfortable for breathing.
When in doubt or if symptoms are observed, get medical advice.

After contact with skin

Take off immediately all contaminated clothing and wash it before reuse.
After contact with skin, wash immediately with plenty of water and soap.
If skin irritation occurs: Get medical advice/attention.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth thoroughly with water.
Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

The following symptoms may occur: Allergic reactions
In case of ingestion: Nausea, Vomiting

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.
alcohol resistant foam
Water spray jet
Dry extinguishing powder
Water mist
Carbon dioxide (CO₂)

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Non-flammable.
Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.
Evacuate area.
Use water spray jet to protect personnel and to cool endangered containers.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

Safety Data Sheet

Alpine Brake Fluid DOT 4

Revision date: 17.03.2021

Product code: MIT0044

Page 4 of 15

6.1. Personal precautions, protective equipment and emergency procedures

General measures

- Keep people at a distance and stay on the windward side.
- Provide adequate ventilation.
- Use personal protection equipment.
- Avoid contact with skin, eyes and clothes.

6.2. Environmental precautions

- Do not allow to enter into surface water or drains.
- In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment

- Stop leak if safe to do so.
- Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Stop leak if safe to do so.

6.4. Reference to other sections

- Safe handling: see section 7
- Personal protection equipment: see section 8
- Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

- If handled uncovered, arrangements with local exhaust ventilation have to be used.
- Do not breathe gas/fumes/vapour/spray.
- Avoid contact with skin, eyes and clothes.
- Use personal protective equipment as required.

Advice on protection against fire and explosion

- No special fire protection measures are necessary.

Further information on handling

- No special fire protection measures are necessary.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

- Keep locked up.
- Keep container tightly closed in a cool, well-ventilated place.
- Keep/Store only in original container.

Hints on joint storage

- Keep away from: Base, Strong acid, Oxidizing agent
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

7.3. Specific end use(s)

- brake fluids

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet

MITAN Mineralöl GmbH

Alpine Brake Fluid DOT 4

Revision date: 17.03.2021

Product code: MIT0044

Page 5 of 15

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
111-77-3	2-(2-Methoxyethoxy)ethanol	10	50.1		TWA (8 h)	WEL
111-46-6	2,2'-Oxydiethanol	23	101		TWA (8 h)	WEL

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
30989-05-0	Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate			
Worker DNEL, long-term	inhalation	systemic	29,1 mg/m ³	
Worker DNEL, long-term	dermal	systemic	8,3 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	7,2 mg/m ³	
Consumer DNEL, long-term	dermal	systemic	4,1 mg/kg bw/day	
Consumer DNEL, long-term	oral	systemic	4,1 mg/kg bw/day	
111-46-6	2,2'-oxybisethanol; diethylene glycol			
Worker DNEL, long-term	inhalation	systemic	44 mg/m ³	
Worker DNEL, long-term	inhalation	local	60 mg/m ³	
Worker DNEL, long-term	dermal	systemic	43 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	12 mg/m ³	
Consumer DNEL, long-term	inhalation	local	12 mg/m ³	
Consumer DNEL, long-term	dermal	systemic	21 mg/kg bw/day	
143-22-6	2-[2-(2-butoxyethoxy)ethoxy]ethanol			
Worker DNEL, long-term	inhalation	systemic	195 mg/m ³	
Worker DNEL, long-term	dermal	systemic	208 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	117 mg/m ³	
Consumer DNEL, long-term	dermal	systemic	125 mg/kg bw/day	
Consumer DNEL, long-term	oral	systemic	12,5 mg/kg bw/day	
111-77-3	2-(2-methoxyethoxy)ethanol			
Worker DNEL, long-term	dermal	systemic	2,22 mg/kg bw/day	
Worker DNEL, long-term	inhalation	systemic	50,1 mg/m ³	
Consumer DNEL, long-term	dermal	systemic	1,33 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	30,1 mg/m ³	
Consumer DNEL, long-term	oral	systemic	7,5 mg/kg bw/day	
26544-38-7	Dihydro-3-(tetrapropenyl)furan-2,5-dione			
Worker DNEL, long-term	dermal	systemic	0,33 mg/kg bw/day	

Safety Data Sheet

MITAN Mineralöl GmbH

Alpine Brake Fluid DOT 4

Revision date: 17.03.2021

Product code: MIT0044

Page 6 of 15

PNEC values

CAS No	Substance	
Environmental compartment		Value
30989-05-0	Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate	
Freshwater		0,211 mg/l
Freshwater (intermittent releases)		2,112 mg/l
Marine water		0,021 mg/l
Freshwater sediment		0,76 mg/kg
Marine sediment		0,076 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		0,028 mg/kg
111-46-6	2,2'-oxybisethanol; diethylene glycol	
Freshwater		10 mg/l
Freshwater (intermittent releases)		10 mg/l
Marine water		1 mg/l
Freshwater sediment		20,9 mg/kg
Marine sediment		2,09 mg/kg
Micro-organisms in sewage treatment plants (STP)		199,5 mg/l
Soil		1,53 mg/kg
143-22-6	2-[2-(2-butoxyethoxy)ethoxy]ethanol	
Freshwater		2 mg/l
Freshwater (intermittent releases)		8,4 mg/l
Marine water		0,2 mg/l
Freshwater sediment		7,7 mg/kg
Marine sediment		0,77 mg/kg
Secondary poisoning		111 mg/kg
Micro-organisms in sewage treatment plants (STP)		200 mg/l
Soil		0,47 mg/kg
111-77-3	2-(2-methoxyethoxy)ethanol	
Freshwater		12 mg/l
Freshwater (intermittent releases)		12 mg/l
Marine water		1,2 mg/l
Freshwater sediment		44,4 mg/kg
Marine sediment		0,44 mg/kg
Secondary poisoning		90 mg/kg
Micro-organisms in sewage treatment plants (STP)		10000 mg/l
Soil		2,1 mg/kg
26544-38-7	Dihydro-3-(tetrapropenyl)furan-2,5-dione	
Freshwater		0,02 mg/l
Freshwater (intermittent releases)		0,2 mg/l

Safety Data Sheet

MITAN Mineralöl GmbH

Alpine Brake Fluid DOT 4

Revision date: 17.03.2021

Product code: MIT0044

Page 7 of 15

Marine water	0,002 mg/l
Freshwater sediment	1,7 mg/kg
Marine sediment	0,17 mg/kg
Micro-organisms in sewage treatment plants (STP)	10 mg/l
Soil	0,2 mg/kg

Additional advice on limit values

Personal air monitoring, Room air monitoring

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately.

Wash hands and face before breaks and after work and take a shower if necessary.

When using do not eat, drink, smoke, sniff.

Eye/face protection

Wear eye/face protection. (EN166)

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. (EN ISO 374)

Suitable material: NBR (Nitrile rubber)

Thickness of the glove material: > 0,3 mm

Breakthrough time: > 8h

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Half-face mask (EN 140)

Filter type: A (EN 141)

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used. (EN 137)

Environmental exposure controls

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:

Liquid

Safety Data Sheet

Alpine Brake Fluid DOT 4

Revision date: 17.03.2021

Product code: MIT0044

Page 8 of 15

Colour:	amber	
Odour:	characteristic	
Odour threshold:	not determined	
pH-Value:		7 - 11,5

Changes in the physical state

Melting point:	< -50 °C
Boiling point or initial boiling point and boiling range:	> 230 °C
Auto-ignition temperature:	> 300 °C
Flash point:	> 100 °C
Sustaining combustion:	No data available

Flammability

Solid/liquid:	not applicable
Gas:	not applicable

Explosive properties

The product is not: Explosive.

Lower explosion limits:	not determined
Upper explosion limits:	not determined

Self-ignition temperature

Solid:	not applicable
Gas:	not applicable

Decomposition temperature:	> 300 °C
----------------------------	----------

Oxidizing properties

The product is not: oxidising.

Vapour pressure:	not determined
Density (at 20 °C):	1,07 g/cm³
Bulk density:	not applicable
Water solubility:	easily soluble

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:	not determined
--	----------------

Viscosity / dynamic:	not determined
----------------------	----------------

Viscosity / kinematic: (at 20 °C)	5-10 mm²/s
--------------------------------------	------------

Relative vapour density:	not determined
--------------------------	----------------

Evaporation rate:	not determined
-------------------	----------------

9.2. Other information

Solid content:	not determined
----------------	----------------

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

Safety Data Sheet

MITAN Mineralöl GmbH

Alpine Brake Fluid DOT 4

Revision date: 17.03.2021

Product code: MIT0044

Page 9 of 15

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Safe handling: see section 7

10.5. Incompatible materials

Incompatible materials: Oxidising agent, strong Acids, Strong alkali

10.6. Hazardous decomposition products

Hazardous decomposition products: Carbon monoxide (CO), Carbon dioxide (CO₂)

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
30989-05-0	Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate				
	oral	LD50 > 2000 mg/kg	Rat	Study report (1995)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (2010)	OECD Guideline 402
111-46-6	2,2'-oxybisethanol; diethylene glycol				
	oral	LD50 16500 mg/kg	Rat	Journal of Industrial Hygiene and Toxicology	
	dermal	LD50 11890 mg/kg	Rabbit		
143-22-6	2-[2-(2-butoxyethoxy)ethoxy]ethanol				
	dermal	LD50 3540 mg/kg	Rabbit	Am Ind Hyg Ass J, 23, 95 (1960)	Study pre-dates guidelines. Similar to o
111-77-3	2-(2-methoxyethoxy)ethanol				
	oral	LD50 7128 mg/kg	Mouse	Study report (1981)	OECD Guideline 401
	dermal	LD50 9404 mg/kg	Rabbit	Study report (1981)	OECD Guideline 402
	inhalation (1 h) vapour	LC50 > 200 mg/l	Rat		

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Contains Dihydro-3-(tetrapropenyl)furan-2,5-dione. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Safety Data Sheet

MITAN Mineralöl GmbH

Alpine Brake Fluid DOT 4

Revision date: 17.03.2021

Product code: MIT0044

Page 10 of 15

Suspected of damaging the unborn child. (Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate; 2-(2-methoxyethoxy)ethanol)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. Special hazards arising from the substance or mixture!

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

Safety Data Sheet

MITAN Mineralöl GmbH

Alpine Brake Fluid DOT 4

Revision date: 17.03.2021

Product code: MIT0044

Page 11 of 15

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
30989-05-0	Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate					
	Acute fish toxicity	LC50 100,3 mg/l	96 h	Oncorhynchus mykiss	Study report (1987)	OECD Guideline 203
	Acute algae toxicity	ErC50 > 224,4 mg/l	72 h	Raphidocelis subcapitata	Study report (1999)	EU Method C.3
	Acute bacteria toxicity	(> 1000 mg/l)	0,5 h	The inoculum of the activated sludge originated fr	Study report (1999)	OECD Guideline 209
111-46-6	2,2'-oxybisethanol; diethylene glycol					
	Acute fish toxicity	LC50 75200 mg/l	96 h	Pimephales promelas	Center for Lake Superior Environmental S	Method: special acute fish toxicity test
	Acute algae toxicity	ErC50 6500 - 13000 mg/l	96 h	Pseudokirchneriella subcapitata	Study report (1982)	other: EPA 600/9-78-018, 1978
	Acute crustacea toxicity	EC50 62630 mg/l	48 h	Daphnia magna	Secondary source (2006)	other: Acute Lethality Test Using Daphni
	Fish toxicity	NOEC 15380 mg/l	7 d	Pimephales promelas	Environ. Toxicology and Chemistry, Vol.	other: EPA 600/4-89/001. U.S. Environmen
	Crustacea toxicity	NOEC 8590 mg/l	7 d	Ceriodaphnia dubia	Environ. Toxicology and Chemistry, Vol.	other: EPA 600/4-89/001. U.S. Environmen
143-22-6	2-[2-(2-butoxyethoxy)ethoxy]ethanol					
	Acute fish toxicity	LC50 2200 - 4600 mg/l	96 h	Leuciscus idus	Study report (1989)	other: German industrial standard test g
	Acute algae toxicity	ErC50 780 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (1999)	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 500 mg/l	48 h	Daphnia magna	Study report (1988)	EU Method C.2
	Crustacea toxicity	NOEC > 100 mg/l	21 d	Daphnia magna	Study report (1999)	OECD Guideline 211
111-77-3	2-(2-methoxyethoxy)ethanol					
	Acute fish toxicity	LC50 5741 mg/l	96 h	Pimephales promelas	Study report (1979)	other: see below
	Acute algae toxicity	ErC50 > 1000 mg/l	96 h	Pseudokirchneriella subcapitata	Study report (1983)	OECD Guideline 201
	Acute crustacea toxicity	EC50 1192 mg/l	48 h	Daphnia magna	Study report (1979)	Followed methods as described in the US
	Acute bacteria toxicity	(> 1000 mg/l)	0,5 h	activated sludge, domestic	Study report (2001)	OECD Guideline 209
26544-38-7	Dihydro-3-(tetrapropenyl)furan-2,5-dione					
	Acute fish toxicity	LC50 > 100 mg/l	96 h	Oncorhynchus mykiss	Study report (2014)	OECD Guideline 203

Safety Data Sheet

MITAN Mineralöl GmbH

Alpine Brake Fluid DOT 4

Revision date: 17.03.2021

Product code: MIT0044

Page 12 of 15

	Acute algae toxicity	ErC50 110 mg/l	96 h	Pseudokirchneriella subcapitata	Study report (1997)	Internal T.R. Wilbury Test Lab Protocol
	Acute bacteria toxicity	(800 mg/l)	3 h	activated sludge, domestic	Study report (1995)	OECD Guideline 209

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
30989-05-0	Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate	-4,37
111-46-6	2,2'-oxybisethanol; diethylene glycol	-1,98
143-22-6	2-[2-(2-butoxyethoxy)ethoxy]ethanol	0,51
111-77-3	2-(2-methoxyethoxy)ethanol	-0,47
26544-38-7	Dihydro-3-(tetrapropenyl)furan-2,5-dione	>= 4,39

BCF

CAS No	Chemical name	BCF	Species	Source
111-46-6	2,2'-oxybisethanol; diethylene glycol	100	Leuciscus idus melanotus	Chemosphere 14(10):

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

No information available.

12.6. Endocrine disrupting properties

No information available.

12.7. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Contaminated packaging

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

Safety Data Sheet

Alpine Brake Fluid DOT 4

Revision date: 17.03.2021

Product code: MIT0044

Page 13 of 15

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 54

2010/75/EU (VOC): 32,98 % (352,886 g/l)

2004/42/EC (VOC): 12,98 % (138,886 g/l)

Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

1 - slightly hazardous to water

Skin resorption/Sensitization:

Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Safety Data Sheet

MITAN Mineralöl GmbH

Alpine Brake Fluid DOT 4

Revision date: 17.03.2021

Product code: MIT0044

Page 14 of 15

Changes

This data sheet contains changes from the previous version in section(s): 1,2,3,4,5,6,7,8,9,10,11,12,13,15,16.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
RID: Regulations concerning the international carriage of dangerous goods by rail
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation
intérieures)
EmS: Emergency Schedules
MFAG: Medical First Aid Guide
ICAO: International Civil Aviation Organization
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
VOC: Volatile Organic Compounds
SVHC: Substance of Very High Concern
For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Repr. 2; H361d	Calculation method

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H361d	Suspected of damaging the unborn child.

Safety Data Sheet

MITAN Mineralöl GmbH

Alpine Brake Fluid DOT 4

Revision date: 17.03.2021

Product code: MIT0044

Page 15 of 15

H413

May cause long lasting harmful effects to aquatic life.

EUH208

Contains Dihydro-3-(tetrapropenyl)furan-2,5-dione. May produce an allergic reaction.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)