

ALPINE® ATF Dexron II D

Automatic Transmission Fluid

Properties

- High viscosity index
- High load carrying capacity and extremely wear-reducing
- Low pour point
- No foam formation
- High thermal stability
- Reliable friction coefficient characteristics
- Excellent viscosity-temperature behaviour
- Excellent oxidation stability
- Neutral towards common sealing materials

Application notes

- Automatic automotive transmission and torque converter
- Manual gearbox, if an ATF is prescribed
- Hydrostatic transmissions
- Power steering
- Hydraulic systems

Observe manufacturer's instructions!

Service description

Recommendation*:

- General Motors Dexron II D
- MB 236.1
- MAN 339 Typ Z-1/V-1
- Allison C-4
- CAT TO-2
- Renk Doromat
- Voith Liste 55.6335.32
- ZF TE-ML 03D / 04D / 11A / 14A / 17C

TYPICAL PARAMETERS	METHODS	UNITS	ALPINE ATF Dexron II D
Thickness at 15°C	DIN 51 757	kg/m³	870
Viscosity 40°C	DIN 51 562	mm²/s	40
Viscosity 100°C	DIN 51 562	mm²/s	8.0
Viscosity index (VI)	DIN ISO 2909	-	171
Pour point	DIN ISO 3016	°C	-45
Flash point COC	DIN ISO 2592	°C	185
Colour	-	-	red

June 2018

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.

MITAN Mineralöl GmbH

Industriestr. 8 • 49577 Ankum • Tel.: 05462/747050 • Fax: 05462/747033
www.mitan-oil.de