

ALPINE® Racing 4T 5W-50

Fully synthetic high performance engine oil for 4-stroke motorcycle engines

Properties

- Exceptional wear protection
- Excellent shear stability
- Optimised friction properties
- Outstanding low temperature performance
- Excellent detergent/dispersing behaviour
- Also suitable for wet clutches
- Effective rust and corrosion protection
- For optimum motor protection

Application notes

ALPINE 4T 5W-50 is especially recommended for the lubrication of 4-stroke motorcycle engines in high-performance motorcycles, even under extreme operating conditions (race track and road).
Observe manufacturer's instructions.

Service description

Specifications:

- API SN
- JASO MA/MA2

TYPICAL PARAMETERS	METHODS	UNITS	ALPINE Racing 4T 5W-50
Density at 15°C	DIN 51 757	kg/m ³	855
Viscosity 40°C	DIN 51 562	mm ² /s	110
Viscosity 100°C	DIN 51 562	mm ² /s	18.5
Viscosity index (VI)	DIN ISO 2909	-	190
Pour point	DIN ISO 3016	°C	-42
Flash point COC	DIN ISO 2592	°C	235
Base number	DIN ISO 3771	mg KOH/g	7.0

June 2018

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.

MITAN Mineralöl GmbH

Industriestr. 8 • 49577 Ankum • Tel.: 05462/747050 • Fax: 05462/747033
www.mitan-oil.de