

ALPINE® RSi 5W-30

HC-synthetic high-performance low viscosity engine oil for passenger cars

Properties

ALPINE RSi 5W-30 is a synthetic high-performance fuel-efficient engine oil of the SAE class 5W-30. Synthetic components and a matching innovative additives ensure compliance with the current practical requirements. The significantly improved engine oil quality of **ALPINE RSi 5W-30** is especially reflected in the further improved wear protection and the improved engine cleanliness, even with extended oil change intervals. The extremely low low-temperature viscosity combined with a safe high-temperature viscosity ensures a high fuel-saving potential.

Application notes

ALPINE RSi 5W-30 is suitable as a high-performance, low-friction engine oil for demanding engines. Recommended for passenger car petrol and diesel engines, including turbo versions and for direct injection engines, under all operating conditions.

Service description

Specifications:

- ACEA A3-/B4
- API SL / CF

Recommendations*:

- BMW Longlife-01
- MB 229.3 / 229.5
- Opel GM-LL-B-025
- Renault RN0700 / RN0710
- VW 502 00 / 505 00

TYPICAL PARAMETERS	METHODS	UNITS	ALPINE RSi 5W-30
Density at 15°C	DIN EN ISO 12185	kg/m ³	855
Viscosity at 40°C	DIN 51 562	mm ² /s	72.5
Viscosity at 100°C	DIN 51 562	mm ² /s	12
Viscosity index (VI)	DIN ISO 2909	-	163
Pour point	ASTM D 7346	°C	-39
Flash point COC	DIN ISO 2592	°C	240
TBN	ASTM D 2896	mg KOH/g	9.8

July 2020

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.