

ALPINE® Sägekettenöl 100

Adhesive special oil for saw chains

Properties

ALPINE saw chain oil 100 is a mineral contact oil with high lubricating film stability and excellent corrosion and wear protection. It also has the following properties:

- Very good cooling effect
- High resistance to ageing
- Good lubricating properties
- Neutral behaviour towards sealing materials and plastics
- High adhesion prevents dripping or spinning
- Dark colour

Application notes

ALPINE saw chain oil 100 is used to lubricate the saw chains on motorised chain saws.

ALPINE saw chain oil 100 is also suitable for low-loaded lubrication points where a contact oil is required.

Observe manufacturer's instructions!

TYPICAL PARAMETERS	METHODS	UNITS	ALPINE Sägekettenöl 100
Density at 15°C	DIN 51 757	kg/m ³	893
Viscosity 40°C	DIN 51 562	mm ² /s	110
Viscosity 100°C	DIN 51 562	mm ² /s	11.5
Pour point	DIN ISO 3016	°C	-24
Flash point COC	DIN ISO 2592	°C	220

June 2018

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.

MITAN Mineralöl GmbH

Industriestr. 8 • 49577 Ankum • Tel.: 05462/747050 • Fax: 05462/747033
www.mitan-oil.de